





ENGINEERED OAK PLANK - COTSWOLD PL04 / PL05 (14mm)

Product definition	Multilayer engineered Oak T&G plank (random lengths)
Grade	BCD
Veneer	European Oak
Core	Poplar / Eucalyptus
Finish	PL04: Golden Oak, hand-scraped and UV lacquered PL05: Natural Oak, brushed and UV oiled
Pack size	1.8m²
Planks per pack	10
Dimensions	14/3 × 125 × 300-1200mm (random lengths)
Profile	Micro-bevelled four-sided T&G $-$ 0.8mm, 45 $^{\circ}$
Length tolerance	± 1.0mm
Width tolerance	± 0.2mm
Thickness tolerance	± 0.3mm
Gap tolerance	± 0.4mm
Underfloor heating	Suitable for use with UFH systems. For further information, please refer to www.grainwoodfloors.co.uk
Warranty	Residential: 25 years / Commercial: 15 years
FSC	Certified
PEFC	Certified

GENERAL

Cleaning, maintenance and installation	Please refer to guidance at www.grainwoodfloors.co.uk
Laying instructions	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which it is to be laid and the correct adhesives to be used.
Please note	Variations in the tonal range between the planks is due to differences that occur naturally in the Oak veneer which enhances the unique character of this engineered flooring product.
Warranty information	All warranties are subject to CCTUK T&C (available on request).
UKTR compliant	All goods are purchased in accordance with UKTR (Timber and Timber Products Placing on the Market Regulations) which came into effect in Great Britain (England, Scotland and Wales) from 1 January 2021, replacing EUTR (European Timber Regulations).

For a brochure, photos and more information, please visit www.grainwoodfloors.co.uk

